
## <sup>2023</sup> MULE PRO-FXT<sup>™</sup> EPS







## POWER

Engine	4-stroke, 3-cylinder, DOHC, liquid-cooled, gas
Displacement	812cc
Bore x Stroke	2.83x2.62 in
<b>Compression Ratio</b>	9.5:1
Maximum Torque	48.0 lb-ft @ 3500 rpm
Fuel System	DFI® with 34mm throttle body
Transmission	Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD, shaft. Dual mode rear differential with differential lock
Engine Braking	Yes
Alternator Output (max)	75 amp

## CAPABILITY

Front Suspension / Wheel Travel	Double wishbone/8.7 in
Rear Suspension / Wheel Travel	Double wishbone/8.5 (L) /8.7 (R) in
Front Tires	26x9.00-12, radial
Rear Tires	26x11.00-12, radial
Park Brake Type	Independent, Mechanical Disc
Steering	Electric Power Steering (EPS), Tilt steering
Front Brakes	Dual Disc, 2 piston caliper
Rear Brakes	Dual Disc, 1 piston caliper
Ground Clearance	10.2 in

Fuel Capacity	7.9 gal
Turning Radius	16.0 ft
Cargo Bed Dimensions (LxWxH)	42.7 x 53.7 x 11.0 in (3-person), 22.0 x 53.7 x 11.0 in (6- person)
Cargo Bed Capacity	999 lb (3-person), 350 lb (6-person), (348 lb for California models)
Load Capacity	1616.3 lb (1263.5 for California models)
Seating Capacity	3-person (1 row), 6 person (2 row)
Towing Capacity	2000 lb
Lighting	(2) Halogen headlights

## DETAILS

Overall Length	133.3 in
Overall Width	64.0 in
Overall Height	77.6 in
Curb Weight	1911.7 lb*
Wheelbase	92.3 in
Instruments	Multi-function display includes digital speedometer, fuel gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, oil pressure warning indicator, fuel injection warning indicator, CVT and EPS warning indicators, neutral, reverse and parking indicators, seatbelt reminder lamps
Wheel Type	Steel
Color Choices	Timberline Green, Bright White
Warranty	Kawasaki Strong 3-Year Limited Warranty
Kawasaki Protection Plus™ (optional)	12, 24 or 36 months

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

All MULE SX<sup>TM</sup> Series side x side's Rollover Protective Structure (ROPS) meets the performance requirements of SAE J1194.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear protective gear appropriate for the use of this vehicle. Never operate under the influence of drugs or alcohol. Protect the environment. The Kawasaki MULE<sup>TM</sup> side x side is an off- highway vehicle only, and is not designed, equipped or manufactured for use on public streets, roads or highways. Obey the laws and regulations that control the use of your vehicle. ©2022 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit Kawasaki.com for full product details.

Scan with camera to view videos, key features and more.

